Renewable Energy in a Petroleum Dominated Society Geothermal in the Middle East

A prifogebeanek	AC	
hate fan	cate	rab t3 75
The exhead sae of	led adj	ace tte ac
eve ded er	calyto	le þ\$ 55
iatici a	rab 303	•
D h a d c h	ſ	jidh e
a b lctb0US\$8,28	2,661.	D b ad o
Peanyes	ate solica	aea
whead agig for 0	છ 5℃.	Ftistoensige

		A A A A A A A A A A A A A A A A A A A
	The product of the pr	
This would find the TOUS of the	1. The Still representations	THE THE THE
	ACTION OF A DESCRIPTION	
	na an a	
% [] CASING		84.00
TENDALLATE:		
	24 20 0 20% J - R823	
May water and the state of the		Tatel Times

Jamie E. Hutchins, P.E., LEED AP

cad pc) Deve is bed intre idade ears The	geo heat	esiziba high s
n hickad ab t2 150m	d eep		
h berhendieged	sh hathe bo	some abtol 700 manport. The	Ç
Orandi 350 meter	ey herdec	ookked at 2° pr 30 nip diec	
Þævlasd 76 daşagelydelagd der tævla		arepoced dy aesad ig bea	
c þ n	totothe sect evaluated 50 daytava	abdctobUS\$6,818,441.	
Bare 6100 l es	procol (abto 5,000 bae to averprota)	y tavane reparer a the	
9 6 1	Figure	es presented on this poster	are for the Þ r

Hole & Casing Details	e & Casing Surface Details Casing		Anchor Casing	Production Casing	Slotted Production Liner
Hole Size (inches)	36"	26	17½"	12¼″	8½"
Hole Depth (metres MD RT)	50	500	1200	2000	2640
Seamless	∙ শিউ≳িিির Detai₊s	<u>- ಇಯ್ಯಿಸ್ಟರ್ನ್ ೧</u> ೯೩೫೦ - ERW	e 1º MON DOUBLES	Seamless	, - ™s' sR: ⊡3sr ' Seamless
26 lb/ft	Weigl	nt i 234,00 lb/ft.	1 33.00 lb/ft.	- 68 lb/ft	47 \b/ft
 []]]]]]]]]]]]]]]]]]]]]]]]]	80~ 1 1 1 1 1	son i III seection III. seection III.	Ghacet. Badel & Control of Stree	≫5≥0 I I St ^{Maldad} Pres	4550
40	96	- 124	98		imate No. of Joints 220 x 15 mm (
Perforation Setting Depth (m MD)					1 inetre blank each end
		. 498	1198	450 to1998	1973 to 264
Casing Cementing	Cemented back to surface.	Cemented back	Cemented back i to surface	Cemented back i to hanger.	Not cemente
l à lling i luis a Seconde III II Science	savadile) III (AP Sym		er ^{ter m} pergel Mus	d Sting based Muc ægs"	Aerated Brin weiter with

The data pested dataped is coletan	npasty. The extedes bed herein			
ae c ențin te pic i	D €S	gþae.	One the ensurements of the ensur	Þæd,
data Nove pheed foot on.				



rst geothermal well only.



