

Geothermal Power Plays

High Temperature Electronics for Downhole Environments

Wade Williams

Southern Methodist University

Dallas, Texas

May 20th, 2015



Joule's Niche:




Markets Served:

>

>

Geothermal Power Plays

Given:




Geothermal drilling, formation evaluation, and downhole monitoring is the most challenging with hottest and hardest demanding conditions.


This environment severely limits the life and performance of electronic components, sub-systems, and turn-key designs.

Given:

LEVELIZED COST OF ELECTRICITY LCOE Formula




I_0 = investment expenditures in the year t ; M_t = O&M expenditures in the year t ; E_t = fuel expenditures in the year t



The definition of high temperD6tDe TJ-.D6to-.c

Applications

High Temperature Downhole Disciplines:



>

>

>


>

>

>

>

>



High Temperature Electronics for Downhole Environments Applications

High Temperature Silicon Components

>

>

200°C with appropriate high temperature

>

>

>

>

>

>

>

>

>

X-Rel Semiconductor

SOI Reliability Assessment

>

>

>

>

High Temp Components:

EVANS CAPACITOR 200°C

>

APEI 225°C

>

>

SPJ Thick Film RESISTORS 300°C

>

UNITED SILICON CARBIDE 260°C

>

VECTRON INTERNATIONAL 230°C

>

VANGUARD ELECTRONICS 220°C

>

X-REL SEMICONDUCTOR 230°C

>

>

CRITERIA LABS HT DIE PACKAGING 230°C

>



High Temperature Sub-Systems And Design Services

Very Little "Off the Shelf" solutions exist above 175°C

>

>

200°C

>

Joule Design Services:

CAPACITOR MODULES 200°C

>

POWER SUPPLIES 200°C

>

SOI DATA ACQUISITION 225°C

>

>

SILICON CARBIDE POWER MODULES 260°C

>

REAL-TIME CLOCK MODULES 180°C

CUSTOM MAGNETICS 220°C

HIGH TEMPERATURE CHARACTERIZATION/AGING 230°C

DIE, MCM AND HYBRID PACKAGING 240°C

DOWNHOLE & SURFACE ELECTRICAL AND MECHANICAL
ENGINEERING SERVICES -40°C to 230°C

>



Conclusion

Cost-competitive energy

requires technology development

>

>

>

>

>

>

>

>

